

# Produktblad

## Armerade rör

Ny betongteknologi i kombination med förbättrade produktionsmetoder har gjort GERMAX-rören mera motståndskraftiga mot korrosion.



## Rakt rör

| Dimension mm   | DN   | Hållfasthetsklass | Kg/st (kg) | Artikelnummer |
|----------------|------|-------------------|------------|---------------|
| 400 PG x 2200  | 400  | 165               | 640        | 820-042216    |
| 600 PG x 2200  | 600  | 165               | 1030       | 820-062216    |
| 500 PG x 2200  | 500  | 165               | 900        | 820-052216    |
| 600 PG x 2200  | 600  | 110               | 1030       | 820-062211    |
| 800 PG x 2200  | 800  | 110               | 1930       | 820-082211    |
| 800 PG x 2200  | 800  | 165               | 1930       | 820-082216    |
| 1000 PG x 2200 | 1000 | 110               | 2420       | 820-102211    |
| 1000 PG x 2200 | 1000 | 165               | 2420       | 820-102216    |
| 1200 PG x 2200 | 1200 | 110               | 3260       | 820-122211    |
| 1200 PG x 2200 | 1200 | 165               | 3260       | 820-122216    |
| 1400 PG x 2200 | 1400 | 110               | 4370       | 820-142211    |
| 1400 PG x 2200 | 1400 | 165               | 4370       | 820-142216    |
| 1600 PG x 1500 | 1600 | 110               | 3670       | 820-161511    |
| 1600 PG x 1500 | 1600 | 165               | 3670       | 820-161516    |
| 1800 GF x 1500 | 1800 | 110               | 4570       | 820-181511    |
| 1800 GF x 1500 | 1800 | 165               | 4570       | 820-181516    |
| 2000 GF x 1500 | 2000 | 110               | 5390       | 820-201511    |
| 2000 GF x 1500 | 2000 | 165               | 5390       | 820-201516    |
| 2200 RF x 1500 | 2200 | 110               | 6100       | 820-221511    |
| 2200 RF x 1500 | 2200 | 165               | 6100       | 820-221516    |
| 2500 PG x 1500 | 2500 | 110               | 9100       | 820-251511    |
| 2500 PG x 1500 | 2500 | 165               | 9100       | 820-251516    |
| 2700 RF x 1500 | 2700 | 110               | 8000       | 820-271511    |
| 2700 RF x 1500 | 2700 | 165               | 8000       | 820-271516    |

## Kortrör

| Dimension mm   | DN   | Hållfasthetsklass | Kg/st (kg) | Artikelnummer |
|----------------|------|-------------------|------------|---------------|
| 400 PG x 500   | 400  | 165               | 140        | 822-0405      |
| 2000 GF x 750  | 2000 | 165               | 2625       | 822-2007      |
| 400 PG x 1000  | 400  | 165               | 290        | 822-0410      |
| 500 PG x 1000  | 500  | 165               | 450        | 822-0510      |
| 600 PG x 1000  | 600  | 165               | 530        | 822-0610      |
| 800 PG x 1000  | 800  | 165               | 825        | 822-0810      |
| 1000 PG x 1000 | 1000 | 165               | 1100       | 822-1010      |
| 1200 PG x 1000 | 1200 | 165               | 1490       | 822-1210      |
| 1400 PG x 1000 | 1400 | 165               | 1910       | 822-1410      |
| 1600 PG x 750  | 1600 | 165               | 1750       | 822-1607      |
| 1800 GF x 750  | 1800 | 165               | 2200       | 822-1807      |

Armerad spetsvändare

| Dimension mm   | DN   | Hållfasthetsklass | Kg/st (kg) | Artikelnummer |
|----------------|------|-------------------|------------|---------------|
| 400x500        | 400  | 200               | 140        | 824-0405      |
| 500x1000       | 500  | 165               | 405        | 824-0510      |
| 600x1000       | 600  | 165               | 540        | 824-0610      |
| 800x1000       | 800  | 165               | 750        | 824-0810      |
| 1000x1000      | 1000 | 165               | 1000       | 824-1010      |
| 1200 PG x 1000 | 1200 | 165               | 1490       | 824-1210      |
| 1400 PG x 1000 | 1400 | 165               | 1910       | 824-1410      |
| 1600 PG x 750  | 1600 | 165               | 1910       | 824-1607      |
| 1800 GF x 750  | 1800 | 165               | 2200       | 824-1807      |
| 2000 GF x 750  | 2000 | 165               | 2625       | 824-2007      |
| 1800x1500      |      |                   | 4400       | 824-1815      |
| 2200x1500      |      | 165               | 6235       | 824-2215      |

| Dimension mm   | DN   | Hållfasthetsklass | Kg/st (kg) | Artikelnummer |
|----------------|------|-------------------|------------|---------------|
| 1400 PG x 2200 | 1400 | 165               | 4115       | 824-91422     |
| 1600 PG x 2200 | 1600 | 165               | 6300       | 824-91622     |

Krokrör PG

| Dimension mm  | DN  | Hållfasthetsklass | Kg/st (kg) | Artikelnummer |
|---------------|-----|-------------------|------------|---------------|
| 500x210 5°    | 500 | 165               | 95         | 826-0505      |
| 500x270 10°   | 500 | 165               | 120        | 826-0510      |
| 500x330 15°   | 500 | 165               | 150        | 826-0515      |
| 500x425 22,5° | 500 | 165               | 190        | 826-0522      |
| 600x220 5°    | 600 | 165               | 120        | 826-0605      |
| 600x285 10°   | 600 | 165               | 160        | 826-0610      |
| 600x355 15°   | 600 | 165               | 190        | 826-0615      |
| 600x440 22,5° | 600 | 165               | 240        | 826-0622      |
| 800x205 5°    | 800 | 165               | 180        | 826-0805      |
| 800x320 10°   | 800 | 165               | 270        | 826-0810      |
| 800x435 15°   | 800 | 165               | 390        | 826-0815      |
| 800x610 22,5° | 800 | 165               | 510        | 826-0822      |

Tätningspropp PG

| Dimension mm | DN   | Hållfasthetsklass | Kg/st (kg) | Artikelnummer |
|--------------|------|-------------------|------------|---------------|
| 500          |      |                   | 65         | 827-0500      |
| 600          |      |                   | 90         | 827-0600      |
| 800          | 800  |                   | 170        | 827-0800      |
| 1000         | 1000 |                   | 280        | 827-1000      |

Fotrör armerat

| Dimension mm   | DN   | Hållfasthetsklass | Kg/st (kg) | Artikelnummer |
|----------------|------|-------------------|------------|---------------|
| 800 PG x 2000  | 800  | 200               | 1945       | 819-082020    |
| 1000 PG x 2200 | 1000 | 165               | 3200       | 819-102216    |
| 1400 PG x 2200 | 1400 | 165               | 5200       | 819-142216    |
| 1600 PG x 2200 | 1600 | 165               | 7100       | 819-162216    |