

Produktblad

Armerade rör

Ny betongteknologi i kombination med förbättrade produktionsmetoder har gjort GERMAX-rören mera motståndskraftiga mot korrosion.



Rakt rör

Dimension mm	DN	Hållfasthetsklass	Kg/st (kg)	Artikelnummer
400 PG x 2200	400	165	640	820-042216
600 PG x 2200	600	165	1030	820-062216
500 PG x 2200	500	165	900	820-052216
600 PG x 2200	600	110	1030	820-062211
800 PG x 2200	800	110	1930	820-082211
800 PG x 2200	800	165	1930	820-082216
1000 PG x 2200	1000	110	2420	820-102211
1000 PG x 2200	1000	165	2420	820-102216
1200 PG x 2200	1200	110	3260	820-122211
1200 PG x 2200	1200	165	3260	820-122216
1400 PG x 2200	1400	110	4370	820-142211
1400 PG x 2200	1400	165	4370	820-142216
1600 PG x 1500	1600	110	3670	820-161511
1600 PG x 1500	1600	165	3670	820-161516
1800 GF x 1500	1800	110	4570	820-181511
1800 GF x 1500	1800	165	4570	820-181516
2000 GF x 1500	2000	110	5390	820-201511
2000 GF x 1500	2000	165	5390	820-201516
2200 RF x 1500	2200	110	6100	820-221511
2200 RF x 1500	2200	165	6100	820-221516
2500 PG x 1500	2500	110	9100	820-251511
2500 PG x 1500	2500	165	9100	820-251516
2700 RF x 1500	2700	110	8000	820-271511
2700 RF x 1500	2700	165	8000	820-271516

Kortrör

Dimension mm	DN	Hållfasthetsklass	Kg/st (kg)	Artikelnummer
400 PG x 500	400	165	140	822-0405
2000 GF x 750	2000	165	2625	822-2007
400 PG x 1000	400	165	290	822-0410
500 PG x 1000	500	165	450	822-0510
600 PG x 1000	600	165	530	822-0610
800 PG x 1000	800	165	825	822-0810
1000 PG x 1000	1000	165	1100	822-1010
1200 PG x 1000	1200	165	1490	822-1210
1400 PG x 1000	1400	165	1910	822-1410
1600 PG x 750	1600	165	1750	822-1607
1800 GF x 750	1800	165	2200	822-1807

Armerad spetsvändare

Dimension mm	DN	Hållfasthetsklass	Kg/st (kg)	Artikelnummer
400x500	400	165	92	824-0405
500x500		165	155	824-0505
500x1000	500	165	405	824-0510
600x1000	600	165	540	824-0610
800x1000	800	165	750	824-0810
1000x1000	1000	165	1000	824-1010
1200 PG x 1000	1200	165	1490	824-1210
1400 PG x 1000	1400	165	1910	824-1410
1600 PG x 750	1600	165	1910	824-1607
1800 GF x 750	1800	165	2200	824-1807
2000 GF x 750	2000	165	2625	824-2007
1800x1500			4400	824-1815
2200x1500		165	6235	824-2215

Dimension mm	DN	Hållfasthetsklass	Kg/st (kg)	Artikelnummer
1400 PG x 2200	1400	165	4115	824-91422
1600 PG x 2200	1600	165	6300	824-91622

Krokrör PG

Dimension mm	DN	Hållfasthetsklass	Kg/st (kg)	Artikelnummer
500x210 5°	500	165	95	826-0505
500x270 10°	500	165	120	826-0510
500x330 15°	500	165	150	826-0515
500x425 22,5°	500	165	190	826-0522
600x220 5°	600	165	120	826-0605
600x285 10°	600	165	160	826-0610
600x355 15°	600	165	190	826-0615
600x440 22,5°	600	165	240	826-0622
800x205 5°	800	165	180	826-0805
800x320 10°	800	165	270	826-0810
800x435 15°	800	165	390	826-0815
800x610 22,5°	800	165	510	826-0822

Tätningpropp PG

Dimension mm	DN	Hållfasthetsklass	Kg/st (kg)	Artikelnummer
500			65	827-0500
600			90	827-0600
800	800		170	827-0800
1000	1000		280	827-1000

Fotrör armerat

Dimension mm	DN	Hållfasthetsklass	Kg/st (kg)	Artikelnummer
800 PG x 2000	800	200	1945	819-082020
1000 PG x 2200	1000	165	3200	819-102216
1400 PG x 2200	1400	165	5200	819-142216
1600 PG x 2200	1600	165	7100	819-162216