

Produktblad

Armerade rör

Armerade rör i betong ger extra styrka i projekt med hög belastning. En hållbar VA-lösning som kombinerar miljövärden med robusthet, lång livslängd och driftsäker funktion.



Rakt rör armerat

Dimension mm	DN	Hållfasthetsklass	Kg/st (kg)	Artikelnummer
400 PG x 2200	400	165	640	820-402216
500 PG x 2200	500	165	880	820-502216
600 PG x 2200	600	110	1025	820-602211
600 PG x 2200	600	165	1025	820-602216
800 PG x 2200	800	110	1920	820-802211
800 PG x 2200	800	165	1920	820-802216
1000 PG x 2200	1000	110	2420	820-102211
1000 PG x 2200	1000	165	2420	820-102216
1200 PG x 2200	1200	110	3260	820-122211
1200 PG x 2200	1200	165	3260	820-122216
1400 PG x 2200	1400	110	4370	820-142211
1400 PG x 2200	1400	165	4370	820-142216
1600 PG x 1500	1600	110	3670	820-161511
1600 PG x 1500	1600	165	3670	820-161516
1800 GF x 1500	1800	110	4570	820-181511
1800 GF x 1500	1800	165	4570	820-181516
2000 GF x 1500	2000	110	5390	820-201511
2000 GF x 1500	2000	165	5390	820-201516
2200 RF x 1500	2200	110	6100	820-221511
2200 RF x 1500	2200	165	6100	820-221516
2500 PG x 1500	2500	110	9100	820-251511
2500 PG x 1500	2500	165	9100	820-251516
2700 RF x 1500	2700	110	8000	820-271511
2700 RF x 1500	2700	165	8000	820-271516

Rakt rör

Dimension mm	DN	Hållfasthetsklass	Kg/st (kg)	Artikelnummer
800 PG x 2200	800	110	1930	820-082211

Armerat kortrör

Dimension mm	DN	Hållfasthetsklass	Kg/st (kg)	Artikelnummer
400 PG x 500	400	165	140	822-400516
400 PG x 1000	400	165	290	822-401016
500 PG x 1000	500	200	390	822-501020
600 PG x 1000	600	165	530	822-601016
800 PG x 1000	800	165	825	822-801016
1000 PG x 1000	1000	165	1250	822-101016
1200 PG x 1000	1200	165	1490	822-121016
1400 PG x 1000	1400	165	1910	822-141016
1600 PG x 750	1600	165	1750	822-160716
1800 GF x 750	1800	165	2200	822-180716
2000 GF x 750	2000	165	2625	822-200716

PG kortrör

Dimension mm	DN	Hållfasthetsklass	Kg/st (kg)	Artikelnummer
600 PG x 1000	600	165	450	822-6010168

Armerat kortrör - PG

Dimension mm	DN	Hållfasthetsklass	Kg/st (kg)	Artikelnummer
500 PG x 1000	500	165	450	822-501016

Armerade spetsvändare

Dimension mm	DN	Hållfasthetsklass	Kg/st (kg)	Artikelnummer
400 PG x 500	400	200	140	824-400520
500 PG x 500	500	165	155	824-500520
600 PG x 1000	600	165	540	824-601016
800 PG x 1000	800	165	750	824-801016
1000 PG x 1000	1000	165	1000	824-101016
1200 PG x 1000	1200	165	1490	824-121016
1400 PG x 1000	1400	165	1910	824-141016
1600 PG x 750	1600	165	1910	824-160716
1800 GF x 750	1800	165	2200	824-180716
2000 GF x 750	2000	165	2625	824-200716
500x1000	500	165	405	824-501016
2200x1500	2200	165	6235	824-221516

Armerade spetsvändare fotrör - PG

Dimension mm	DN	Hållfasthetsklass	Kg/st (kg)	Artikelnummer
1400 PG x 2200	1400	165	4115	824-91422
1600 PG x 2200	1600	165	6300	824-91622

Armerade krokrör - PG

Dimension mm	DN	Hållfasthetsklass	Kg/st (kg)	Artikelnummer
600x5°	600	165	120	826-6005
600x10°	600	165	160	826-6010
600x15°	600	165	190	826-6015
600x22°	600	165	240	826-6022
800x5°	800	165	180	826-8005
800x10°	800	165	270	826-8010
800x15°	800	165	390	826-8015
800x22°	800	165	510	826-8022
1000x5°	1000	165	205	826-1005
1000x10°	1000	165	330	826-1010
1000x15°	1000	165	460	826-1015
1000x22°	1000	165	650	826-1022

Armerade fotrör - PG

Dimension mm	DN	Hållfasthetsklass	Kg/st (kg)	Artikelnummer
800 PG x 2000	800	200	1945	819-802020
1200 PG x 2200	1200	165	3855	819-122216
1400 PG x 2200	1400	165	5200	819-142216
1600 PG x 2200	1600	165	7100	819-162216

Dimension mm	DN	Hållfasthetsklass	Kg/st (kg)	Artikelnummer
1000 PG x 2200	1000	165	3200	819-102216