

Armerade rör – GERMAX

Ny betongteknologi i kombination med förbättrade produktionsmetoder har gjort GERMAX-rören mera motståndskraftiga mot korrosion.



Rakt rör

| Dimension mm | DN | Hållfasthetsklass | Kg/st (kg) | Artikelnummer |
|----------------|------|-------------------|------------|---------------|
| 400 PG x 2200 | 400 | 165 | 640 | 820-042216 |
| 600 PG x 2200 | 600 | 165 | 1030 | 820-062216 |
| 500 PG x 2200 | 500 | 165 | 900 | 820-052216 |
| 600 PG x 2200 | 600 | 110 | 1030 | 820-062211 |
| 800 PG x 2200 | 800 | 110 | 1930 | 820-082211 |
| 800 PG x 2200 | 800 | 165 | 1930 | 820-082216 |
| 1000 PG x 2200 | 1000 | 110 | 2420 | 820-102211 |
| 1000 PG x 2200 | 1000 | 165 | 2420 | 820-102216 |
| 1200 PG x 2200 | 1200 | 110 | 3260 | 820-122211 |
| 1200 PG x 2200 | 1200 | 165 | 3260 | 820-122216 |
| 1400 PG x 2200 | 1400 | 110 | 4370 | 820-142211 |
| 1400 PG x 2200 | 1400 | 165 | 4370 | 820-142216 |
| 1600 PG x 1500 | 1600 | 110 | 3670 | 820-161511 |
| 1600 PG x 1500 | 1600 | 165 | 3670 | 820-161516 |
| 1800 GF x 1500 | 1800 | 110 | 4570 | 820-181511 |
| 1800 GF x 1500 | 1800 | 165 | 4570 | 820-181516 |
| 2000 GF x 1500 | 2000 | 110 | 5390 | 820-201511 |
| 2000 GF x 1500 | 2000 | 165 | 5390 | 820-201516 |
| 2200 RF x 1500 | 2200 | 110 | 6100 | 820-221511 |
| 2200 RF x 1500 | 2200 | 165 | 6100 | 820-221516 |
| 2500 PG x 1500 | 2500 | 110 | 9100 | 820-251511 |
| 2500 PG x 1500 | 2500 | 165 | 9100 | 820-251516 |
| 2700 RF x 1500 | 2700 | 110 | 8000 | 820-271511 |
| 2700 RF x 1500 | 2700 | 165 | 8000 | 820-271516 |

Kortrör

| Dimension mm | DN | Hållfasthetsklass | Kg/st (kg) | Artikelnummer |
|----------------|------|-------------------|------------|---------------|
| 400 PG x 500 | 400 | 165 | 140 | 822-0405 |
| 2000 GF x 750 | 2000 | 165 | 2625 | 822-2007 |
| 400 PG x 1000 | 400 | 165 | 290 | 822-0410 |
| 500 PG x 1000 | 500 | 165 | 450 | 822-0510 |
| 600 PG x 1000 | 600 | 165 | 530 | 822-0610 |
| 800 PG x 1000 | 800 | 165 | 825 | 822-0810 |
| 1000 PG x 1000 | 1000 | 165 | 1100 | 822-1010 |
| 1200 PG x 1000 | 1200 | 165 | 1490 | 822-1210 |
| 1400 PG x 1000 | 1400 | 165 | 1910 | 822-1410 |
| 1600 PG x 750 | 1600 | 165 | 1750 | 822-1607 |
| 1800 GF x 750 | 1800 | 165 | 2200 | 822-1807 |

Armerad spetsvändare

| Dimension mm | DN | Hållfasthetsklass | Kg/st (kg) | Artikelnummer |
|----------------|------|-------------------|------------|---------------|
| 400x500 | 400 | 165 | 92 | 824-0405 |
| 500x500 | | 165 | 155 | 824-0505 |
| 500x1000 | 500 | 165 | 405 | 824-0510 |
| 600x1000 | 600 | 165 | 540 | 824-0610 |
| 800x1000 | 800 | 165 | 750 | 824-0810 |
| 1000x1000 | 1000 | 165 | 1000 | 824-1010 |
| 1200 PG x 1000 | 1200 | 165 | 1490 | 824-1210 |
| 1400 PG x 1000 | 1400 | 165 | 1910 | 824-1410 |
| 1600 PG x 750 | 1600 | 165 | 1910 | 824-1607 |
| 1800 GF x 750 | 1800 | 165 | 2200 | 824-1807 |
| 2000 GF x 750 | 2000 | 165 | 2625 | 824-2007 |
| 1800x1500 | | | 4400 | 824-1815 |
| 2200x1500 | | 165 | 6235 | 824-2215 |

| Dimension mm | DN | Hållfasthetsklass | Kg/st (kg) | Artikelnummer |
|----------------|------|-------------------|------------|---------------|
| 1400 PG x 2200 | 1400 | 165 | 4115 | 824-91422 |
| 1600 PG x 2200 | 1600 | 165 | 6300 | 824-91622 |

Krokrör PG

| Dimension mm | DN | Hållfasthetsklass | Kg/st (kg) | Artikelnummer |
|---------------|-----|-------------------|------------|---------------|
| 500x210 5° | 500 | 165 | 95 | 826-0505 |
| 500x270 10° | 500 | 165 | 120 | 826-0510 |
| 500x330 15° | 500 | 165 | 150 | 826-0515 |
| 500x425 22,5° | 500 | 165 | 190 | 826-0522 |
| 600x220 5° | 600 | 165 | 120 | 826-0605 |
| 600x285 10° | 600 | 165 | 160 | 826-0610 |
| 600x355 15° | 600 | 165 | 190 | 826-0615 |
| 600x440 22,5° | 600 | 165 | 240 | 826-0622 |
| 800x205 5° | 800 | 165 | 180 | 826-0805 |
| 800x320 10° | 800 | 165 | 270 | 826-0810 |
| 800x435 15° | 800 | 165 | 390 | 826-0815 |
| 800x610 22,5° | 800 | 165 | 510 | 826-0822 |

Tätningpropp PG

| Dimension mm | DN | Hållfasthetsklass | Kg/st (kg) | Artikelnummer |
|--------------|------|-------------------|------------|---------------|
| 500 | | | 65 | 827-0500 |
| 600 | | | 90 | 827-0600 |
| 800 | 800 | | 170 | 827-0800 |
| 1000 | 1000 | | 280 | 827-1000 |

Fotrör armerat

| Dimension mm | DN | Hållfasthetsklass | Kg/st (kg) | Artikelnummer |
|----------------|------|-------------------|------------|---------------|
| 800 PG x 2000 | 800 | 200 | 1945 | 819-082020 |
| 1000 PG x 2200 | 1000 | 165 | 3200 | 819-102216 |
| 1400 PG x 2200 | 1400 | 165 | 5200 | 819-142216 |
| 1600 PG x 2200 | 1600 | 165 | 7100 | 819-162216 |